



HCN Series NON-POLARIZED ELECTROLYTIC CAPACITOR

Non-polarized with general temperature +85°C


Load life of 1000 hours

RoHS & REACH compliant, Halogen-free

SPECIFICATIONS

Items	Characteristics				
Operation Temperature Range	-40 ~ +85°C				
Voltage Range	6.3 ~ 50V				
Capacitance Range	0.1 ~ 100μF				
Capacitance Tolerance	±20% at 120Hz, 20°C				
Leakage Current	Leakage current ≤0.05CV or 10μA, whichever is greater (after 2 minutes application of rated voltage at 20°C) C: Nominal capacitance (μF) V: Rated voltage (V)				
Dissipation Factor (tan δ)	Measurement frequency : 120Hz, Temperature : 20°C				
	Rated Voltage (V)	6.3	10	16, 25	35, 50
Stability at Low Temperature	Measurement frequency : 120Hz				
	Rated Voltage (V)	6.3	10	16, 25	35, 50
Load Life	After 1000 hours application of the rated voltage at 85°C (the polarity needs to exchange every 250 hours), they meet the characteristics listed below.				
	Capacitance Change	Within ±20% of initial value			
Shelf Life	After leaving capacitors under no load at 85°C for 1000 hours, they meet the specified value for load life characteristics listed above.				
	Dissipation Factor	200% or less of initial specified value			
Resistance to Soldering Heat	After reflow soldering and restored at room temperature, they meet the characteristics listed below.				
	Leakage Current	initial specified value or less			
Marking	Black print on the case top.				

DRAWING (Unit: mm)



*1. Voltage mark for 6.3V is [6V]

*2. Applicable to $\varnothing 6.3 \times 7.7$

DIMENSIONS (Unit: mm)

ØD x L	4 x 5.4	5 x 5.4	6.3 x 5.4	6.3 x 7.7
A	2.0	2.2	2.6	2.6
B	4.3	5.3	6.6	6.6
C	4.3	5.3	6.6	6.6
E ± 0.2	1.0	1.4	1.9	1.9
L	5.4	5.4	5.4	7.7



DIMENSIONS & MAXIMUM PERMISSIBLE RIPPLE CURRENT

μF	WV Code	6.3		10		16		25		35		50	
		Case size	Ripple current	Case size	Ripple current	Case size	Ripple current	Case size	Ripple current	Case size	Ripple current	Case size	Ripple current
0.1	104											4 × 5.4	1.0
0.22	224											4 × 5.4	2.0
0.33	334											4 × 5.4	2.8
0.47	474											4 × 5.4	4.0
1	105											4 × 5.4	8.4
2.2	225									4 × 5.4	8.4	5 × 5.4	13
3.3	335							5 × 5.4	12	5 × 5.4	16	5 × 5.4	17
4.7	475					4 × 5.4	12	5 × 5.4	16	5 × 5.4	18	6.3 × 5.4	20
10	106			4 × 5.4	17	5 × 5.4	23	6.3 × 5.4	27	6.3 × 5.4	29	6.3 × 7.7	36
22	226	5 × 5.4	28	6.3 × 5.4	33	6.3 × 5.4	37	6.3 × 7.7	50	6.3 × 7.7	54		
33	336	6.3 × 5.4	37	6.3 × 5.4	41	6.3 × 5.4	49	6.3 × 7.7	61				
47	476	6.3 × 5.4	45	6.3 × 7.7	61	6.3 × 7.7	75						
100	107	6.3 × 7.7	82	6.3 × 7.7	85								

•Case size ØD×L(mm), ripple current (mA rms) at 85°C, 120Hz

FREQUENCY COEFFICIENT OF ALLOWABLE RIPPLE CURRENT

Frequency	50Hz	120Hz	300Hz	1KHz	10KHz~
Coefficient	0.70	1.00	1.17	1.36	1.50

The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5~10°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced.

◆ How to order

HCN	106	M	0035	0405	R	-
↓	↓	↓	↓	↓	↓	↓
<u>Type</u>	<u>Capacitance code</u>	<u>Tolerance</u>	<u>Rated Voltage</u>	<u>Size Code</u>	<u>Package</u>	<u>Additional characters may be added for special requirements</u>
HCN	pF Code: 1st two digits represent significant figures 3rd digit represents multiplier (number of zeros to follow) 106 = 10uF 107 = 100uF	M: +/-20%	Code 0035: 35VDC For DC Voltage 0006: 6.3VDC 0035: 35VDC 0050: 50VDC	Code 0405: Size 4x5.4mm Size for V-chip E-cap 0405: Size 4x5.4mm 0605: Size 6.3x5.4mm 0607: Size 6.3x7.7mm	R: Tape & Reel	

Note: Specification is subject to change without further notice. For more details and updates, please visit our website.